




FAG

23332-BEA-XL-MA1-T41B

Spherical Roller Bearing

X-life

Technical information



Your current product variant

| | | |
|--|--------------|-----------------------------------|
| Design | BEA | With lose center lip ring |
| Bore type | Z | Cylindrical |
| Cage | MA1 | Solid brass cage |
| Radial internal clearance | C4 (Group 4) | Internal clearance larger than C3 |
| Relubrication facility | Standard | |
| Locating feature, bearing outer ring | Without | |
| Handling thread holes | Without | |
| Special material | Standard | |
| Spherical roller bearing for vibrating screens | T41A | For vibrating screens |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 160 mm | Bore diameter |
| D | 340 mm | Outside diameter |
| B | 136 mm | Width |
| C _r | 2.000.000 N | Basic dynamic load rating, radial |
| C _{0r} | 2.370.000 N | Basic static load rating, radial |
| C _{ur} | 186.000 N | Fatigue load limit, radial |
| n _G | 2.010 1/min | Limiting speed |
| ≈m | 62,6 kg | Weight |



Mounting dimensions

| | | |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 192 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 323 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 3 mm | Maximum recess radius |

Dimensions

| | | |
|------------|----------|-----------------------------|
| r_{\min} | 4 mm | Minimum chamfer dimension |
| D_1 | 280,8 mm | Bore diameter outer ring |
| d_s | 9,5 mm | Diameter lubrication hole |
| n_s | 17,7 mm | Width of lubricating groove |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 200 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--|
| e | 0,42 | Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y |
| Y_1 | 1,6 | Dynamic axial load factor |
| Y_2 | 2,38 | Dynamic axial load factor |
| Y_0 | 1,56 | Static axial load factor |



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment