

**SL192307-XL**

Cylindrical roller bearing

Technical information



Your current product variant

Number of rows	1	Single-row design
----------------	---	-------------------

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	80 mm	Outside diameter
B	31 mm	Width
C_r	126.000 N	Basic dynamic load rating, radial
C_{0r}	110.000 N	Basic static load rating, radial
C_{ur}	20.500 N	Fatigue load limit, radial
n_G	5.800 1/min	Limiting speed
n_{gr}	3.600 1/min	Reference speed
m	0,74 kg	Weight








Dimensions

D_1	65,8 mm	Shoulder diameter outer ring
$D_{a \max}$	65,5 mm	Maximum diameter of housing shoulder
d_1	50,7 mm	Shoulder diameter inner ring
$d_{a \min}$	44,5 mm	Minimum diameter shaft shoulder
$d_{c \min}$	50,5 mm	Minimum shaft shoulder
F	44,7 mm	Raceway diameter inner ring
$r_{a \max}$	1,5 mm	Maximum fillet radius
r_{\min}	1,5 mm	Minimum chamfer dimension
s	2 mm	Axial displacement

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

-  F_r Radial load
-  F_a Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed