

**FAG****6006-C>V**

Deep groove ball bearing

Deep groove ball bearing 60...-C, single row,  
Generation C, steel sheet metal cage

## Technical information



## Your current product variant

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Sealing	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	P6	Class6 (P6), better then PN
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	55 mm	Outside diameter
B	13 mm	Width
C <sub>r</sub>	14.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	8.300 N	Basic static load rating, radial
C <sub>ur</sub>	500 N	Fatigue load limit, radial
n <sub>G</sub>	20.100 1/min	Limiting speed
n <sub>gr</sub>	13.800 1/min	Reference speed
≈m	0,108 kg	Weight



### Mounting dimensions

$d_{a \min}$	34,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	50,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$D_1$	48 mm	Shoulder diameter outer ring
$D_2$	50,22 mm	Caliber diameter outer ring
$d_1$	38 mm	Shoulder diameter inner ring
$d_2$	36,67 mm	Caliber diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	14,8	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed