

IMAGE
COMING SOON

FAG

NU232-E-XL-MCA-C3

Cylindrical roller bearing

Cylindrical roller bearing NU20..-E-XL-MCA, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Technical information

Your current product variant

Design	Standard	
Cage	MCA	Messing Käfig, einteilig, bordgeführt am Außenring
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	160 mm	Bore diameter
D	290 mm	Outside diameter
B	48 mm	Width
C _r	590.000 N	Basic dynamic load rating, radial
C _{0r}	670.000 N	Basic static load rating, radial
C _{ur}	80.000 N	Fatigue load limit, radial
n _G	4.200 1/min	Limiting speed
n _{gr}	2.160 1/min	Reference speed
≈m	14,22 kg	Weight



Mounting dimensions

$d_{a \min}$	174 mm	Minimum diameter shaft shoulder
$d_{a \max}$	192 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	197 mm	Minimum shaft shoulder
$D_{a \max}$	276 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$r_{a1 \max}$	2,5 mm	Maximum recess radius

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
$r_{1 \min}$	3 mm	Minimum chamfer dimension
s	4,1 mm	Axial displacement
E	259 mm	Raceway diameter outer ring
F	195 mm	Raceway diameter inner ring
$D_{1 \min}$	249,6 mm	Minimum rib diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	150 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed