

**FAG****6301-C-C3>V**

Deep groove ball bearing

Deep groove ball bearing 63...C, single row,  
Generation C, steel sheet metal cage

## Technical information



## Your current product variant

Version code	>V	Not marked on bearing
Changed internal design	C	GenerationC
Type of Seal	Without	Not sealed
Cage	JN	Steel sheet metal
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	12 mm	Bore diameter
D	37 mm	Outside diameter
B	12 mm	Width
C <sub>r</sub>	11.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	4.200 N	Basic static load rating, radial
C <sub>ur</sub>	290 N	Fatigue load limit, radial
n <sub>G</sub>	31.000 1/min	Limiting speed
n <sub>gr</sub>	21.900 1/min	Reference speed
≈m	0,055 kg	Weight



### Mounting dimensions

$d_{a \min}$	17,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	31,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$D_1$	30,06 mm	Shoulder diameter outer ring
$D_2$	32 mm	Caliber diameter outer ring
$d_1$	18,94 mm	Shoulder diameter inner ring
$d_2$	17,97 mm	Caliber diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	11,1	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Grease Lubrication
	Oil Lubrication
	Not sealed