

**FAG****61813-2RZ**

Deep groove ball bearing

Deep groove ball bearing 618..-2RZ, single row, shields, steel sheet metal cage

Technical information



Your current product variant

Sealing	2RZ	Non-contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	85 mm	Outside diameter
B	10 mm	Width
C _r	13.000 N	Basic dynamic load rating, radial
C _{0r}	12.000 N	Basic static load rating, radial
C _{ur}	780 N	Fatigue load limit, radial
n _G	9.600 1/min	Limiting speed
n _{gr}	5.700 1/min	Reference speed
m	0,131 kg	Weight



Mounting dimensions

$d_{a \min}$	68,2 mm	Minimum diameter shaft shoulder
$D_{a \max}$	81,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius

Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
D_1	78,57 mm	Shoulder diameter outer ring
D_2	80,5 mm	Caliber diameter outer ring
d_1	71,6 mm	Shoulder diameter inner ring

Temperature range

T_{\min}	-20 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Calculation factors

f_0	16,2	Calculation factor
-------	------	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides