




GIHRK50-DO [↗](#)

Rod end

Hydraulic rod end, with thread clamping device, right hand thread, requiring maintenance, sliding contact surface: steel/steel, open design

Technical information



Your current product variant

Clampable	Clampable	
Maintenance	Maintenance required	
Lubrication nipple	DIN71412-AM6 (tapered grease nipple)	
Slotted	Slotted, both sides	
Thread Pitch	Right-hand thread	
Sealing	Without	
Mounting	Internal thread	
Radial internal clearance	CN (Group N)	Normal internal clearance

Main Dimensions & Performance Data

C_r	204.000 N	Basic dynamic load rating, radial
C_{0r}	333.000 N	Basic static load rating, radial
d	50 mm	Bore diameter bearing
d_2	116 mm	Outer eye diameter
l_4	168 mm	Total length internal thread head
D	75 mm	Outside diameter bearing
B	35 mm	Width inner ring
$\approx m$	3,8 kg	Weight



Dimensions

α	6 °	Tilt angle
C ₁	40 mm	Width of the rod end
d _K	66 mm	Ball diameter
d ₃	M45x1,5	Thread size
d ₄	61 mm	Shank diameter
d ₅	90 mm	Shank diameter, large
d ₇	M12x35	Diameter screw clamp
h ₁	105 mm	Shank Length Internal thread head
l ₃	46 mm	Thread length Internal thread
l ₇	55 mm	Distance drilling with/shaft start
d _{UT}	-0,012 mm	Bore diameter bearing, lower tolerance
d _T	0,012	Bore diameter bearing, tolerance
d _{OT}	0 mm	Bore diameter bearing, upper tolerance
B _{UT}	-0,12 mm	Width inner ring, lower tolerance
B _{OT}	0 mm	Width inner ring, upper tolerance
M _A	110 Nm	Tightening torque
G _r	0,030 - 0,12 mm	Radial Clearance
G _{rmin}	0,03 mm	Radial clearance, minimum
G _{rmax}	0,12 mm	Radial clearance, maximum

Mounting dimensions








r _{1smin}	0,6 mm	Edge Spacing
d ₁	56 mm	Outer flange diameter inner ring

Temperature range

T _{min}	-60 °C	Operating temperature min.
T _{max}	200 °C	Operating temperature max.



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment