

**FAG****61821-2RZ**

Deep groove ball bearing

Deep groove ball bearing 618..-2RZ, single row, shields, steel sheet metal cage

## Technical information



## Your current product variant

Sealing	2RZ	Non-contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	105 mm	Bore diameter
D	130 mm	Outside diameter
B	13 mm	Width
C <sub>r</sub>	22.100 N	Basic dynamic load rating, radial
C <sub>0r</sub>	23.600 N	Basic static load rating, radial
C <sub>ur</sub>	1.320 N	Fatigue load limit, radial
n <sub>G</sub>	6.000 1/min	Limiting speed
n <sub>gr</sub>	3.900 1/min	Reference speed
m	0,331 kg	Weight



### Mounting dimensions

$d_{a \min}$	109,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	125,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$D_1$	122,07 mm	Shoulder diameter outer ring
$D_2$	124,2 mm	Caliber diameter outer ring
$d_1$	113,2 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	15,9	Calculation factor
-------	------	--------------------

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides