

**GE120-DO**

Spherical plain bearing

Radial spherical plain bearing, requiring maintenance, sliding contact surface: steel/steel, DIN ISO 12240-1, dimension series E, open design High-performance: For highest load rating and lifetime demands

Technical information



Your current product variant

| | |
|---------------------------|--|
| Maintenance | Maintenance required |
| Material | Steel |
| Sealing | Without |
| Radial internal clearance | CN (Group N) Normal internal clearance |
| Coating | Durotect M Inner- and outer ring coated with Durotect M (Manganese Phosphate) |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 120 mm | Bore diameter bearing |
| D | 180 mm | Outside diameter bearing |
| B | 85 mm | Width inner ring |
| C _r | 1.240.000 N | Basic dynamic load rating, radial |
| C _{0r} | 4.760.000 N | Basic static load rating, radial |
| m | 7,236 kg | Weight |

Mounting dimensions

| | | |
|--------------------|----------|-------------------------------|
| r _{1min} | 1 mm | Edge Spacing |
| r _{2min} | 1 mm | Edge Spacing |
| d _{a max} | 135,5 mm | Connection measure Inner ring |
| D _{a min} | 150 mm | Housing Connection Diameter |



Dimensions

| | | |
|------------|---------------|--|
| C | 70 mm | Width Outer ring |
| d_K | 160 mm | Ball diameter |
| α | 6 ° | Tilt angle |
| d_{OT} | 0 mm | Bore diameter bearing, upper tolerance |
| d_{UT} | -0,02 mm | Bore diameter bearing, lower tolerance |
| D_{OT} | 0 mm | Outside diameter, upper tolerance |
| D_{UT} | -0,025 mm | Outside diameter, lower tolerance |
| B_{OT} | 0 mm | Width inner ring, upper tolerance |
| B_{UT} | -0,2 mm | Width inner ring, lower tolerance |
| C_{OT} | 0 mm | Width outer ring, upper tolerance |
| C_{UT} | -0,5 mm | Width outer ring, lower tolerance |
| G_r | 0,085 - 0,165 | Radial Clearance |
| G_{rmax} | 0,165 mm | Radial clearance, maximum |
| G_{rmin} | 0,085 mm | Radial clearance, minimum |

Temperature range

| | | |
|-----------|--------|----------------------------|
| T_{min} | -60 °C | Operating temperature min. |
| T_{max} | 200 °C | Operating temperature max. |

Characteristics

-  F_r Radial load
-  F_a Axial load in one direction
-  F_a Axial load in two directions
-  Grease Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment