


**GE12-AX**

## Spherical plain bearing



Axial spherical plain bearing, requiring maintenance, sliding contact surface: steel/steel

## Technical information

**Your current product variant**

Maintenance	Maintenance required
Coating	Durotect M Inner- and outer ring coated with Durotect M (Manganese Phosphate)

**Main Dimensions & Performance Data**

d	12 mm	Inner diameter bearing
D	35 mm	Outside diameter bearing
T	13 mm	Height
C <sub>a</sub>	42.100 N	Basic dynamic load rating, axial
C <sub>0a</sub>	162.000 N	Basic static load rating, axial
≈m	70,18 g	Weight

**Mounting dimensions**

r <sub>1smin</sub>	0,6 mm	Edge Spacing
r <sub>2smin</sub>	0,2 mm	Edge Spacing
d <sub>a max</sub>	24 mm	Connection measure Inner ring
D <sub>a min</sub>	21,5 mm	Housing Connection Diameter



### Dimensions

$d_K$	37 mm	Ball diameter
$d_3$	24	Front surface diameter of shaft washer
$D_1$	19,5 mm	Inner diameter of housing washer
B	9,3 mm	Width Inner ring
C	9 mm	Width Outer ring
s	8 mm	Plane Surface Spacing
A	4 mm	Distance lubrication Bore
$\alpha$	9 °	Tilt angle
$d_{OT}$	0 mm	Bore diameter bearing, upper tolerance
$d_{UT}$	-0,008 mm	Bore diameter bearing, lower tolerance
$D_{OT}$	0 mm	Outer diameter, upper tolerance
$D_{UT}$	-0,011 mm	Outside diameter, lower tolerance
$T_{OT}$	0 mm	Height, upper tolerance
$T_{UT}$	-0,4 mm	Height, lower tolerance
$C_{UT}$	0 mm	Width outer ring, upper tolerance
$C_{OT}$	-0,24 mm	Width outer ring, lower tolerance
$B_{OT}$	0 mm	Width inner ring, upper tolerance
$B_{UT}$	-0,24 mm	Width inner ring, lower tolerance
$d_2$	32 mm	Connection measure Inner ring

### Temperature range

$T_{min}$	-60 °C	Operating temperature min.
$T_{max}$	200 °C	Operating temperature max.



### Characteristics

---



Radial load



Axial load in one direction



Grease Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment