

**FAG****61704-2RSR-HLC**

Deep groove ball bearing

Deep groove ball bearing 617..-2RSR, single row, seals, steel sheet metal cage

Technical information

**Your current product variant**

Logistical code	HLC	-
Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Lubricating grease	
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

Main Dimensions & Performance Data

d	20 mm	Bore diameter
D	27 mm	Outside diameter
B	4 mm	Width
C _r	1.010 N	Basic dynamic load rating, radial
C _{0r}	722 N	Basic static load rating, radial
C _{ur}	20,5 N	Fatigue load limit, radial
n _G	12.000 1/min	Limiting speed
≈m	6,4 g	Weight



Mounting dimensions

$d_{a \min}$	21,4 mm	Minimum diameter shaft shoulder
$D_{a \max}$	25,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,2 mm	Maximum fillet radius

Dimensions

r_{\min}	0,2 mm	Minimum chamfer dimension
D_1	24,6 mm	Shoulder diameter outer ring
D_2	25,3 mm	Caliber diameter outer ring
d_1	22,36 mm	Shoulder diameter inner ring







Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.

Calculation factors

f_0	8,7	Calculation factor
-------	-----	--------------------

Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides