

**FAG****61911-2RSR**

Deep groove ball bearing

Deep groove ball bearing 619..-2RSR, single row, seals, steel sheet metal cage

## Technical information



## Your current product variant

Sealing	2RSR	Contact seal on both sides
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA13	Ball bearing and insert bearing grease
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	55 mm	Bore diameter
D	80 mm	Outside diameter
B	13 mm	Width
C <sub>r</sub>	17.700 N	Basic dynamic load rating, radial
C <sub>0r</sub>	14.100 N	Basic static load rating, radial
C <sub>ur</sub>	780 N	Fatigue load limit, radial
n <sub>G</sub>	4.250 1/min	Limiting speed
m	0,18 kg	Weight

## Mounting dimensions

d <sub>a min</sub>	59,6 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	75,4 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	1 mm	Maximum fillet radius



## Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$D_1$	71,98 mm	Shoulder diameter outer ring
$D_2$	74,2 mm	Caliber diameter outer ring
$d_1$	63,2 mm	Shoulder diameter inner ring

## Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

## Calculation factors

$f_0$	16,3	Calculation factor
-------	------	--------------------

## Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides