

**FAG****6207-2RSR**

Deep groove ball bearing

Deep groove ball bearing 62...-2RSR, single row, seals, steel sheet metal cage

Technical information



Your current product variant

| | | |
|----------------------------------|--------------|---|
| Sealing | 2RSR | Contact seal on both sides |
| Cage | JN | Steel sheet metal |
| Tolerance class | PN | Normal (PN) |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | GA13 | Ball bearing and insert bearing grease |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Bore type | Z | Cylindrical |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 35 mm | Bore diameter |
| D | 72 mm | Outside diameter |
| B | 17 mm | Width |
| C _r | 27.500 N | Basic dynamic load rating, radial |
| C _{0r} | 15.300 N | Basic static load rating, radial |
| C _{ur} | 950 N | Fatigue load limit, radial |
| n _G | 5.700 1/min | Limiting speed |
| m | 0,283 kg | Weight |

Mounting dimensions

| | | |
|--------------------|-------|--------------------------------------|
| d _{a min} | 42 mm | Minimum diameter shaft shoulder |
| D _{a max} | 65 mm | Maximum diameter of housing shoulder |
| r _{a max} | 1 mm | Maximum fillet radius |



Dimensions

| | | |
|------------|----------|------------------------------|
| r_{\min} | 1,1 mm | Minimum chamfer dimension |
| D_1 | 60,66 mm | Shoulder diameter outer ring |
| D_2 | 63,34 mm | Caliber diameter outer ring |
| d_1 | 47,2 mm | Shoulder diameter inner ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -20 °C | Operating temperature min. |
| T_{\max} | 100 °C | Operating temperature max. |

Calculation factors

| | | |
|-------|------|--------------------|
| f_0 | 13,8 | Calculation factor |
|-------|------|--------------------|

Characteristics

| | |
|---|--|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Lifetime lubrication, freedom from maintenance |
|  | Grease Lubrication |
|  | Sealed on both sides |