

**FAG****6003-RSR**

Deep groove ball bearing

Deep groove ball bearing 60...-RSR, single row, seal, steel sheet metal cage

## Technical information



## Your current product variant

Sealing	RSR	Contact seal on one side
Cage	JN	Steel sheet metal
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	Without	Bearing not greased
Radial internal clearance	CN (Group N)	Normal internal clearance
Bore type	Z	Cylindrical

## Main Dimensions &amp; Performance Data

d	17 mm	Bore diameter
D	35 mm	Outside diameter
B	10 mm	Width
C <sub>r</sub>	6.400 N	Basic dynamic load rating, radial
C <sub>0r</sub>	3.250 N	Basic static load rating, radial
C <sub>ur</sub>	162 N	Fatigue load limit, radial
n <sub>G</sub>	11.800 1/min	Limiting speed
m	37,51 g	Weight

## Mounting dimensions

d <sub>a min</sub>	19 mm	Minimum diameter shaft shoulder
D <sub>a max</sub>	33 mm	Maximum diameter of housing shoulder
r <sub>a max</sub>	0,3 mm	Maximum fillet radius



### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$D_1$	29,51 mm	Shoulder diameter outer ring
$D_2$	30,81 mm	Caliber diameter outer ring
$d_1$	22,65 mm	Shoulder diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Calculation factors

$f_0$	14,3	Calculation factor
-------	------	--------------------

### Characteristics



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Sealed on one side