

**FAG****UC202**

## Radial insert ball bearing

Radial insert ball bearings UC, spherical outer ring, location by grub screws, RSR seals on both sides

## Technical information

**Main Dimensions & Performance Data**

d	15 mm	Bore diameter
D <sub>SP</sub>	47 mm	Outside diameter
B	31 mm	Width
C <sub>0r</sub>	6.600 N	Basic static load rating, radial
C <sub>ur</sub>	345 N	Fatigue load limit, radial
C <sub>r</sub>	13.600 N	Basic dynamic load rating, radial
≈m	0,188 kg	Weight

**Dimensions**

C	17 mm	Width, outer ring
C <sub>2</sub>	16,8 mm	Sealing total width
S	12,7 mm	Distance raceway
d <sub>1</sub>	27,56 mm	Rib diameter inner ring
C <sub>a</sub>	4,2 mm	Distance to lubrication hole
A	5 mm	Distance thread
W	3 mm	Width of flats

**Temperature range**

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	100 °C	Operating temperature max.



### Calculation factors

---

$f_0$	13,1	Calculation factor
-------	------	--------------------

### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides



Static angular error and misalignment