


IMAGE  
COMING SOON**GNE100-KRR-B-FA107**

Radial insert ball bearing

Radial insert ball bearing GNE...KRR-B

## Technical information

**Main Dimensions & Performance Data**

d	100 mm	Bore diameter
D <sub>SP</sub>	215 mm	Outside diameter
B	86 mm	Width
C <sub>0r</sub>	131.000 N	Basic static load rating, radial
C <sub>ur</sub>	5.800 N	Fatigue load limit, radial
B <sub>1</sub>	109,4 mm	Locking collar total width
C <sub>r</sub>	155.000 N	Basic dynamic load rating, radial
≈m	11,41 kg	Weight

**Dimensions**

C	49 mm	Width, outer ring
C <sub>2</sub>	59,4 mm	Sealing total width
S	39,5 mm	Distance raceway
d <sub>1</sub>	137,06 mm	Rib diameter inner ring
D <sub>1</sub>	182,8 mm	Outside diameter seal
C <sub>a</sub>	16,7 mm	Distance to lubrication hole
d <sub>3</sub>	145 mm	Outside diameter locking collar/locknut
W	6 mm	Width of flats










### Temperature range

$T_{min}$	-20 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Calculation factors

$f_0$	12,3	Calculation factor
-------	------	--------------------

### Characteristics

-   $F_r$  Radial load
-   $F_a$  Axial load in one direction
-   $F_a$  Axial load in two directions
-   $L_h$  Lifetime lubrication, freedom from maintenance
-  Grease Lubrication
-  Sealed on both sides
-  Static angular error and misalignment