


IMAGE  
COMING SOON**GRAE40-NPP-B-FA107**

Radial insert ball bearing

Radial insert ball bearing GRAE...NPP-B

## Technical information

**Main Dimensions & Performance Data**

d	40 mm	Bore diameter
D <sub>SP</sub>	80 mm	Outside diameter
B	30,2 mm	Width
C <sub>0r</sub>	19.800 N	Basic static load rating, radial
C <sub>ur</sub>	1.030 N	Fatigue load limit, radial
B <sub>1</sub>	43,8 mm	Locking collar total width
C <sub>r</sub>	34.500 N	Basic dynamic load rating, radial
≈m	0,62 kg	Weight

**Dimensions**

C	21 mm	Width, outer ring
S	11 mm	Distance raceway
d <sub>2</sub>	49,4 mm	Rib diameter sealing inner ring
C <sub>a</sub>	6,4 mm	Distance to lubrication hole
d <sub>3</sub>	58 mm	Outside diameter locking collar/locknut
W	5 mm	Width of flats

**Temperature range**

T <sub>min</sub>	-20 °C	Operating temperature min.
T <sub>max</sub>	120 °C	Operating temperature max.



### Calculation factors

---

$f_0$	13,6	Calculation factor
-------	------	--------------------

### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides



Static angular error and misalignment