



**FAG****7006-B-XL-2RS-TVP**

Angular contact ball bearing

Angular contact ball bearing 70..-B-XL-2RS-TVP, single row, X-life, seals, plastic cage

**X-life**

## Technical information



## Your current product variant

Design variant	B	B
Sealing	2RS	Contact seal on both sides
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA14	Ball bearing grease, low noise

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	55 mm	Outside diameter
B	13 mm	Width
$C_r$	19.900 N	Basic dynamic load rating, radial
$C_{0r}$	13.400 N	Basic static load rating, radial
$C_{ur}$	930 N	Fatigue load limit, radial
$n_G$	6.900 1/min	Limiting speed
$\approx m$	0,112 kg	Weight



### Mounting dimensions

$d_{a \min}$	34,6 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	50,4 mm	Maximum diameter of housing shoulder
$D_{b \max}$	51,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,6 mm	Maximum fillet radius of housing






### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$r_{1 \min}$	0,6 mm	Minimum chamfer dimension
$D_1$	47,05 mm	Shoulder diameter on outer ring wide side face
$D_2$	47,7 mm	Caliber diameter on outer ring wide side face
$D_3$	51,93 mm	Caliber diameter on outer ring small side face
$d_1$	41,26 mm	Shoulder diameter on inner ring wide side face
$d_2$	38,04 mm	Caliber diameter on inner ring wide side face
$a$	24,9 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides