




Technical information



Your current product variant

Design variant	B	B
Sealing	Without	Not sealed
Cage	TVP	Solid cage made of glass-fiber reinforced polyamid PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	Without	Bearing not greased

Main Dimensions & Performance Data

d	25 mm	Bore diameter
D	47 mm	Outside diameter
B	12 mm	Width
C_r	16.000 N	Basic dynamic load rating, radial
C_{0r}	9.900 N	Basic static load rating, radial
C_{ur}	690 N	Fatigue load limit, radial
n_G	19.900 1/min	Limiting speed
n_{gr}	12.000 1/min	Reference speed
$\approx m$	0,072 kg	Weight



Mounting dimensions

$d_{a \min}$	28,2 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	43,8 mm	Maximum diameter of housing shoulder
$D_{b \max}$	45 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,6 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,3 mm	Maximum fillet radius of housing






Dimensions

r_{\min}	0,6 mm	Minimum chamfer dimension
$r_{1 \min}$	0,3 mm	Minimum chamfer dimension
D_1	39,83 mm	Shoulder diameter on outer ring wide side face
D_2	40,5 mm	Caliber diameter on outer ring wide side face
D_3	44,81 mm	Caliber diameter on outer ring small side face
d_1	33,94 mm	Shoulder diameter on inner ring wide side face
d_2	31,52 mm	Caliber diameter on inner ring wide side face
a	21,5 mm	Distance between the apexes of the pressure cones
α	40 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed