



**FAG****7306-B-XL-MP-UO**

Angular contact ball bearing

Schrägkugellager 73...-B-XL-MP, einreihig, X-life, Massivkäfig Messing

**X-life**

## Teknik bilgiler



## Ihre aktuelle Produktvariante

Design variant	B	B
Sealing	Without	Not sealed
Cage	MP	Solid brass cage, ball guided
Tolerance class	P6	Class 6 (ISO 492:2023)
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Bearing with matched conditions for fitting in pairs	UO	Bearing set clearance-free in O or X arrangement
Lubricant	Without	Bearing not greased

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	72 mm	Outside diameter
B	19 mm	Width
C <sub>r</sub>	35.500 N	Basic dynamic load rating, radial
C <sub>0r</sub>	20.100 N	Basic static load rating, radial
C <sub>ur</sub>	1.390 N	Fatigue load limit, radial
n <sub>G</sub>	17.600 1/min	Limiting speed
n <sub>gr</sub>	8.700 1/min	Reference speed
m	0,37 kg	Gewicht



### Mounting dimensions

$d_{a \min}$	37 mm	Minimum diameter of shaft shoulder
$D_{a \max}$	65 mm	Maximum diameter of housing shoulder
$D_{b \max}$	67,8 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum fillet radius of shaft
$r_{a1 \max}$	0,6 mm	Maximum fillet radius of housing

### Dimensions

$r_{\min}$	1,1 mm	Minimum chamfer dimension
$r_1 \min$	0,6 mm	Minimum chamfer dimension
$D_1$	55,9 mm	Shoulder diameter on outer ring wide side face
$d_1$	47,12 mm	Shoulder diameter on inner ring wide side face
$a$	30,9 mm	Distance between the apexes of the pressure cones
$\alpha$	40 °	Contact angle






### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Additional information

$A_{\min}$	0 $\mu\text{m}$	Axial clearance per set min.
Tol (+)	8 $\mu\text{m}$	Tolerance for axial clearance or preload per set

### Eigenschaften

	Radiale Last
	Axiale Last aus einer Richtung
	Fettschmierung
	Ölschmierung
	Nicht abgedichtet