

**3002-2RS**

Angular contact ball bearing

Angular contact ball bearing 30...-B-2RS-TVH,  
double row, seals, plastic cage

## Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Sealing	2RS	Contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA14	Ball bearing grease, low noise
Axial internal clearance	CN	Group N (CN)

**Main Dimensions & Performance Data**

d	15 mm	Bore diameter
D	32 mm	Outside diameter
B	13 mm	Width
$C_r$	8.500 N	Basic dynamic load rating, radial
$C_{0r}$	5.400 N	Basic static load rating, radial
$C_{ur}$	280 N	Fatigue load limit, radial
$n_G$	12.900 1/min	Limiting speed
$\approx m$	0,043 kg	Weight



### Mounting dimensions

$d_{a \min}$	17 mm	Minimum diameter shaft shoulder
$D_{a \max}$	30 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$D_1$	27,23 mm	Shoulder diameter outer ring
$D_2$	27,84 mm	Caliber diameter outer ring
$d_1$	21,3 mm	Shoulder diameter inner ring
$d_2$	19,88 mm	Caliber diameter inner ring
$a$	16,3 mm	Distance between the apexes of the pressure cones
$\alpha$	25 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides