

**FAG****3208-BD-XL**

Angular contact ball bearing

Angular contact ball bearing 32.-BD-XL,
double row, X-life, steel sheet metal cage**X-life**

Technical information



Your current product variant

| | | |
|----------------------------------|---------|---|
| Design variant | B | Bearing without filling slot |
| Changed internal design | D | D |
| Sealing | Without | Not sealed |
| Cage | JH | Steel sheet metal |
| Tolerance class | P6 | Class 6 (ISO 492:2023) |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | Without | Bearing not greased |
| Axial internal clearance | CN | Group N (CN) |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 40 mm | Bore diameter |
| D | 80 mm | Outside diameter |
| B | 30,2 mm | Width |
| C _r | 51.000 N | Basic dynamic load rating, radial |
| C _{0r} | 38.000 N | Basic static load rating, radial |
| C _{ur} | 2.650 N | Fatigue load limit, radial |
| n _G | 8.900 1/min | Limiting speed |
| n _{gr} | 9.100 1/min | Reference speed |
| ≈m | 0,593 kg | Weight |



Mounting dimensions

| | | |
|--------------|-------|--------------------------------------|
| $d_{a \min}$ | 47 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 73 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|----------|---|
| r_{\min} | 1,1 mm | Minimum chamfer dimension |
| D_1 | 69,6 mm | Shoulder diameter outer ring |
| D_2 | 72,57 mm | Caliber diameter outer ring |
| d_1 | 54,9 mm | Shoulder diameter inner ring |
| d_2 | 52,83 mm | Caliber diameter inner ring |
| a | 47,4 mm | Distance between the apexes of the pressure cones |
| α | 30 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 120 °C | Operating temperature max. |

Characteristics

| | |
|---|------------------------------|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Grease Lubrication |
|  | Oil Lubrication |
|  | Not sealed |