

**FAG****3210-BD-XL-2HRS**

Angular contact ball bearing



Angular contact ball bearing 32..-BD-XL-2HRS, double row, X-life, seals, steel sheet metal cage

X-life

Technical information



Your current product variant

| | | |
|----------------------------------|------|---|
| Design variant | B | Bearing without filling slot |
| Changed internal design | D | D |
| Sealing | 2HRS | Contact seal on both sides |
| Cage | JH | Steel sheet metal |
| Tolerance class | P6 | Class 6 (ISO 492:2023) |
| Dimensional / heat stabilization | SN | Rings dimensional stabilized up to 120° |
| Lubricant | GA13 | Ball bearing and insert bearing grease |
| Axial internal clearance | CN | Group N (CN) |

Main Dimensions & Performance Data

| | | |
|-----------------|-------------|-----------------------------------|
| d | 50 mm | Bore diameter |
| D | 90 mm | Outside diameter |
| B | 30,2 mm | Width |
| C _r | 53.000 N | Basic dynamic load rating, radial |
| C _{0r} | 44.000 N | Basic static load rating, radial |
| C _{ur} | 3.050 N | Fatigue load limit, radial |
| n _G | 5.900 1/min | Limiting speed |
| ≈m | 0,698 kg | Weight |



Mounting dimensions

| | | |
|--------------|-------|--------------------------------------|
| $d_{a \min}$ | 57 mm | Minimum diameter shaft shoulder |
| $D_{a \max}$ | 83 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1 mm | Maximum fillet radius |

Dimensions

| | | |
|------------|----------|---|
| r_{\min} | 1,1 mm | Minimum chamfer dimension |
| D_1 | 80,1 mm | Shoulder diameter outer ring |
| D_2 | 82,91 mm | Caliber diameter outer ring |
| d_1 | 64,9 mm | Shoulder diameter inner ring |
| d_2 | 62,83 mm | Caliber diameter inner ring |
| a | 53,2 mm | Distance between the apexes of the pressure cones |
| α | 30 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -20 °C | Operating temperature min. |
| T_{\max} | 100 °C | Operating temperature max. |

Characteristics

| | |
|---|--|
|  | Radial load |
|  | Axial load in one direction |
|  | Axial load in two directions |
|  | Lifetime lubrication, freedom from maintenance |
|  | Grease Lubrication |
|  | Sealed on both sides |