

**FAG****3212-BD-XL-2Z-TVH**

Angular contact ball bearing

Angular contact ball bearing 32..-BD-XL-2Z-TVH, double row, X-life, shields, plastic cage

**X-life**

## Technical information



## Your current product variant

Design variant	B	Bearing without filling slot
Changed internal design	D	D
Sealing	2Z	Non-contact shield on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	P6	Class6 (P6), better than PN
Dimensional / heat stabilization	S0	Rings dimensional stabilized up to 150°
Lubricant	GA13	Ball bearing and insert bearing grease
Axial internal clearance	CN	Group N (CN)

## Main Dimensions &amp; Performance Data

d	60 mm	Bore diameter
D	110 mm	Outside diameter
B	36,5 mm	Width
C <sub>r</sub>	75.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	64.000 N	Basic static load rating, radial
C <sub>ur</sub>	4.400 N	Fatigue load limit, radial
n <sub>G</sub>	4.750 1/min	Limiting speed
n <sub>gr</sub>	6.700 1/min	Reference speed
m	1,27 kg	Weight



### Mounting dimensions

$d_{a \min}$	69 mm	Minimum diameter shaft shoulder
$D_{a \max}$	101 mm	Maximum diameter of housing shoulder
$r_{a \max}$	1,5 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	1,5 mm	Minimum chamfer dimension
$D_1$	97,02 mm	Shoulder diameter outer ring
$D_2$	100,51 mm	Caliber diameter outer ring
$d_1$	78,99 mm	Shoulder diameter inner ring
$d_2$	76,58 mm	Caliber diameter inner ring
$a$	64,7 mm	Distance between the apexes of the pressure cones
$\alpha$	30 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides