


**3807-2Z-C3**

## Angular contact ball bearing

Angular contact ball bearing 38..-B-2RZ-TVH,  
double row, shields, plastic cage

## Technical information

**Your current product variant**

Design variant	B	Bearing without filling slot
Sealing	2RZ	Non-contact seal on both sides
Cage	TVH	Solid cage made of glass-fiber reinforced polyamide PA66
Tolerance class	PN	Normal (ISO 492:2023)
Dimensional / heat stabilization	SN	Rings dimensional stabilized up to 120°
Lubricant	GA14	Ball bearing grease, low noise
Axial internal clearance	C3	Group 3 (C3), bigger than CN

**Main Dimensions & Performance Data**

d	35 mm	Bore diameter
D	47 mm	Outside diameter
B	10 mm	Width
$C_r$	6.500 N	Basic dynamic load rating, radial
$C_{0r}$	6.800 N	Basic static load rating, radial
$C_{ur}$	375 N	Fatigue load limit, radial
$n_G$	11.700 1/min	Limiting speed
$n_{gr}$	7.400 1/min	Reference speed
$\approx m$	0,041 kg	Weight



### Mounting dimensions

$d_{a \min}$	37 mm	Minimum diameter shaft shoulder
$D_{a \max}$	45 mm	Maximum diameter of housing shoulder
$r_{a \max}$	0,3 mm	Maximum fillet radius

### Dimensions

$r_{\min}$	0,3 mm	Minimum chamfer dimension
$D_1$	43 mm	Shoulder diameter outer ring
$D_2$	44,05 mm	Caliber diameter outer ring
$d_1$	39 mm	Shoulder diameter inner ring
$d_2$	37,5 mm	Caliber diameter inner ring
$a$	22,6 mm	Distance between the apexes of the pressure cones
$\alpha$	25 °	Contact angle

### Temperature range

$T_{\min}$	-20 °C	Operating temperature min.
$T_{\max}$	100 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Axial load in two directions
	Lifetime lubrication, freedom from maintenance
	Grease Lubrication
	Sealed on both sides