

**FAG****B71922-C-2RSD-T-P4S-UL**

## Spindle bearing

Spindle bearing B719...-C-2RSD, adjusted, in pairs or sets, contact angle  $\alpha = 15^\circ$ , lip seals on both sides, non-contact, restricted tolerances

## Technical information



## Your current product variant

|                         |      |  |
|-------------------------|------|--|
| Preload                 | L    | Preload light  |
| Contact angle           | C    | Contact angle 15°  |
| Tolerance class         | P4S  | Tolerance class P4S, FAG standard better than P4 to ISO 492:2023 |
| Cage                    | T    | Laminated fabric cage  |
| Arrangement bearing set | U    | Single bearing   |
| Lubricant               | GA21 | Grease for super precision bearings, standard                    |

## Main Dimensions &amp; Performance Data

|                 |             |                                       |
|-----------------|-------------|---------------------------------------|
| d               | 110 mm      | Bore diameter                         |
| D               | 150 mm      | Outside diameter                      |
| B               | 20 mm       | Width                                 |
| $C_r$           | 61.000 N    | Basic dynamic load rating, radial     |
| $C_{0r}$        | 47.000 N    | Basic static load rating, radial      |
| $C_{ur}$        | 4.350 N     | Fatigue load limit, radial            |
| $n_G$<br>Grease | 8.500 1/min | Limiting speed for grease lubrication |
| $\approx m$     | 0,85 kg     | Weight                                |



### Mounting dimensions

|               |         |   |
|---------------|---------|---|
| $d_a$         | 117 mm  | Diameter shaft shoulder                           |
| $d_a$         | h12     | Diameter shaft shoulder clearance                 |
| $D_a$         | 143 mm  | Shoulder diameter outer ring                      |
| $D_a$         | H12     | Shoulder diameter outer ring clearance            |
| $r_{a \max}$  | 0,6 mm  | Maximum recess radius                             |
| $r_{a1 \max}$ | 0,6 mm  | Maximum recess radius                             |
| $a$           | 27,4 mm | Distance between the apexes of the pressure cones |

### Dimensions

|              |        |                           |
|--------------|--------|---------------------------|
| $r_{\min}$   | 1,1 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1,1 mm | Minimum chamfer dimension |
| $\alpha$     | 15 °   | Contact angle             |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 80 °C  | Operating temperature max. |

### Additional information

|           |                |                       |
|-----------|----------------|-----------------------|
| $F_{VL}$  | 314 N          | Preload force light   |
| $F_{VM}$  | 1.038 N        | Preload force medium  |
| $F_{VH}$  | 2.102 N        | Preload force heavy   |
| $K_{aEL}$ | 961 N          | Lift-off force light  |
| $K_{aEM}$ | 3.415 N        | Lift-off force medium |
| $K_{aEH}$ | 7.373 N        | Lift-off force heavy  |
| $c_{aL}$  | 96 N/ $\mu$ m  | Axial rigidity light  |
| $c_{aM}$  | 163 N/ $\mu$ m | Axial rigidity medium |
| $c_{aH}$  | 232 N/ $\mu$ m | Axial rigidity heavy  |



### Characteristics

---



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides