

**FAG****B7204-E-2RSD-T-P4S-UL**

## Spindle bearing

Spindle bearing B72...-E-2RSD, adjusted, in pairs or sets, contact angle  $\alpha = 25^\circ$ , lip seals on both sides, non-contact, restricted tolerances

## Technical information



## Your current product variant

Preload	L	Preload light
Contact angle	E	Contact angle $25^\circ$
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Cage	T	Laminated fabric cage
Arrangement bearing set	U	Single bearing
Lubricant	GA21	Grease for super precision bearings, standard

## Main Dimensions &amp; Performance Data

d	20 mm	Bore diameter
D	47 mm	Outside diameter
B	14 mm	Width
$C_r$	16.500 N	Basic dynamic load rating, radial
$C_{0r}$	7.700 N	Basic static load rating, radial
$C_{ur}$	810 N	Fatigue load limit, radial
$n_G$ Grease	30.000 1/min	Limiting speed for grease lubrication
$\approx m$	100 g	Weight



### Mounting dimensions

$d_a$	26,5 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	40,5 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,3 mm	Maximum recess radius
$a$	14,9 mm	Distance between the apexes of the pressure cones

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$r_{1 \min}$	1 mm	Minimum chamfer dimension
$\alpha$	25 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	80 °C	Operating temperature max.

### Additional information

$F_{VL}$	107 N	Preload force light
$F_{VM}$	398 N	Preload force medium
$F_{VH}$	848 N	Preload force heavy
$K_{aEL}$	313 N	Lift-off force light
$K_{aEM}$	1.212 N	Lift-off force medium
$K_{aEH}$	2.686 N	Lift-off force heavy
$c_{aL}$	64 N/μm	Axial rigidity light
$c_{aM}$	106 N/μm	Axial rigidity medium
$c_{aH}$	146 N/μm	Axial rigidity heavy



### Characteristics

---



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides