


**FAG****HSS71916-C-T-P4S-UL**

High speed spindle bearing

High speed spindle bearing HSS719...-C, adjusted, in pairs or sets, contact angle $\alpha = 15^\circ$, lip seals on both sides, non-contact, restricted tolerances

Technical information



Your current product variant

| | | |
|-------------------------|------|--|
| Contact angle | C | Contact angle 15° |
| Sealing | 2RSD | Non-contact sealed on both sides and greased "for life" |
| Cage | T | Laminated fabric cage |
| Tolerance class | P4S | Tolerance class P4S, FAG standard better than P4 to ISO 492:2023 |
| Arrangement bearing set | U | Single bearing |
| Preload | L | Preload light |
| Lubricant | GA21 | Grease for super precision bearings, standard |

Main Dimensions & Performance Data

| | | |
|-----------------|--------------|---------------------------------------|
| d | 80 mm | Bore diameter |
| D | 110 mm | Outside diameter |
| B | 16 mm | Width |
| C_r | 20.300 N | Basic dynamic load rating, radial |
| C_{0r} | 15.500 N | Basic static load rating, radial |
| C_{ur} | 1.640 N | Fatigue load limit, radial |
| n_G Grease | 17.000 1/min | Limiting speed for grease lubrication |
| n_G | 26.000 1/min | Limiting speed |
| $\approx m$ | 0,381 kg | Weight |



Mounting dimensions

| | | |
|---------------|---------|---|
| d_a | 86 mm | Diameter shaft shoulder |
| d_a | h12 | Diameter shaft shoulder clearance |
| D_a | 104 mm | Shoulder diameter outer ring |
| D_a | H12 | Shoulder diameter outer ring clearance |
| $r_{a \max}$ | 0,6 mm | Maximum recess radius |
| $r_{a1 \max}$ | 0,3 mm | Maximum recess radius |
| a | 20,7 mm | Distance between the apexes of the pressure cones |

Dimensions

| | | |
|--------------|------|---------------------------|
| r_{\min} | 1 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1 mm | Minimum chamfer dimension |
| α | 15 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 80 °C | Operating temperature max. |

Additional information

| | | |
|-----------|----------|-----------------------|
| F_{VL} | 71 N | Preload force light |
| F_{VM} | 213 N | Preload force medium |
| F_{VH} | 426 N | Preload force heavy |
| K_{aEL} | 212 N | Lift-off force light |
| K_{aEM} | 666 N | Lift-off force medium |
| K_{aEH} | 1.385 N | Lift-off force heavy |
| c_{aL} | 52 N/μm | Axial rigidity light |
| c_{aM} | 82 N/μm | Axial rigidity medium |
| c_{aH} | 112 N/μm | Axial rigidity heavy |



Characteristics



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides