

**FAG****HSS71917-E-T-P4S-UL**

High speed spindle bearing

High speed spindle bearing HSS719..-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, lip seals on both sides, non-contact, restricted tolerances

Technical information



Your current product variant

| | | |
|-------------------------|------|--|
| Contact angle | E | Contact angle 25° |
| Sealing | 2RSD | Non-contact sealed on both sides and greased "for life" |
| Cage | T | Laminated fabric cage |
| Tolerance class | P4S | Tolerance class P4S, FAG standard better than P4 to ISO 492:2023 |
| Arrangement bearing set | U | Single bearing |
| Preload | L | Preload light |
| Lubricant | GA21 | Grease for super precision bearings, standard |

Main Dimensions & Performance Data

| | | |
|--------------------------|--------------|---------------------------------------|
| d | 85 mm | Bore diameter |
| D | 120 mm | Outside diameter |
| B | 18 mm | Width |
| C _r | 20.000 N | Basic dynamic load rating, radial |
| C _{0r} | 16.000 N | Basic static load rating, radial |
| C _{ur} | 1.670 N | Fatigue load limit, radial |
| n _G Grease | 14.000 1/min | Limiting speed for grease lubrication |
| n _G | 22.000 1/min | Limiting speed |
| ≈m | 0,62 kg | Weight |



Mounting dimensions

| | | |
|---------------|---------|---|
| d_a | 92 mm | Diameter shaft shoulder |
| d_a | h12 | Diameter shaft shoulder clearance |
| D_a | 114 mm | Shoulder diameter outer ring |
| D_a | H12 | Shoulder diameter outer ring clearance |
| $r_{a \max}$ | 0,6 mm | Maximum recess radius |
| $r_{a1 \max}$ | 0,6 mm | Maximum recess radius |
| a | 32,9 mm | Distance between the apexes of the pressure cones |

Dimensions

| | | |
|--------------|--------|---------------------------|
| r_{\min} | 1,1 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1,1 mm | Minimum chamfer dimension |
| α | 25 ° | Contact angle |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 80 °C | Operating temperature max. |

Additional information

| | | |
|-----------|----------|-----------------------|
| F_{VL} | 117 N | Preload force light |
| F_{VM} | 352 N | Preload force medium |
| F_{VH} | 704 N | Preload force heavy |
| K_{aEL} | 338 N | Lift-off force light |
| K_{aEM} | 1.032 N | Lift-off force medium |
| K_{aEH} | 2.102 N | Lift-off force heavy |
| c_{aL} | 140 N/μm | Axial rigidity light |
| c_{aM} | 208 N/μm | Axial rigidity medium |
| c_{aH} | 270 N/μm | Axial rigidity heavy |



Characteristics



Radial load



Axial load in one direction



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides