

**FAG****HC7013-E-T-P4S-UL**

High speed spindle bearing

High speed spindle bearing HC70..-E, adjusted, in pairs or sets, contact angle $\alpha = 25^\circ$, with ceramic balls, restricted tolerances

Technical information




Your current product variant

Preload	L	Preload light
Contact angle	E	Contact angle 25°
Sealing	Without	Not sealed
Cage	T	Laminated fabric cage
Tolerance class	P4S	Tolerance class P4S, FAG standard better than P4 to ISO 492:2023
Arrangement bearing set	U	Single bearing

Main Dimensions & Performance Data

d	65 mm	Bore diameter
D	100 mm	Outside diameter
B	18 mm	Width
C_r	18.200 N	Basic dynamic load rating, radial
C_{0r}	12.200 N	Basic static load rating, radial
C_{ur}	980 N	Fatigue load limit, radial
n_G Grease	22.000 1/min	Limiting speed for grease lubrication
n_G Oil	34.000 1/min	Limiting speed for oil lubrication
$\approx m$	0,424 kg	Weight





Mounting dimensions

d_a	72 mm	Diameter shaft shoulder
d_a	h12	Diameter shaft shoulder clearance
D_a	93 mm	Shoulder diameter outer ring
D_a	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,6 mm	Maximum recess radius
$E_{tk \min}$	78,5 mm	Minimum diameter injection pitch
$E_{tk \max}$	80,2 mm	Maximum diameter injection pitch
$E_{tk1 \min}$	75,9 mm	Minimum diameter injection pitch
$E_{tk1 \max}$	80,2 mm	Maximum diameter injection pitch
a	28,2 mm	Distance between the apexes of the pressure cones

Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
$r_{1 \min}$	1,1 mm	Minimum chamfer dimension
α	25 °	Contact angle

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	100 °C	Operating temperature max.



Additional information

F_{VL}	74 N	Preload force light
F_{VM}	223 N	Preload force medium
F_{VH}	445 N	Preload force heavy
K_{aEL}	213 N	Lift-off force light
K_{aEM}	647 N	Lift-off force medium
K_{aEH}	1.313 N	Lift-off force heavy
c_{aL}	118 N/ μ m	Axial rigidity light
c_{aM}	173 N/ μ m	Axial rigidity medium
c_{aH}	224 N/ μ m	Axial rigidity heavy

Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed