



FAG

NU1012-XL-M1

Cylindrical roller bearing

Cylindrical roller bearing NU..-XL-M1, with cage, single row, non-locating bearing, 2 ribs on outer ring, 0 ribs on inner ring (smooth), type NU, Running accuracy in P6

X-life

Technical information



Your current product variant

| | | |
|--------------------------------|--------------|------------------------------------|
| Design | Standard | |
| Cage | M1 | Two Piece Brass Cage Roller Guided |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Tolerance class | PN | Normal (PN) |
| Number of rolling element rows | 1 | Single-row design |

Main Dimensions & Performance Data

| | | |
|-------------|--------------|-----------------------------------|
| d | 60 mm | Bore diameter |
| D | 95 mm | Outside diameter |
| B | 18 mm | Width |
| C_r | 52.000 N | Basic dynamic load rating, radial |
| C_{0r} | 55.000 N | Basic static load rating, radial |
| C_{ur} | 7.400 N | Fatigue load limit, radial |
| n_G | 14.800 1/min | Limiting speed |
| n_{gr} | 6.400 1/min | Reference speed |
| $\approx m$ | 460,29 g | Weight |



Mounting dimensions

| | | |
|---------------|--------|--------------------------------------|
| $d_{a \min}$ | 65 mm | Minimum diameter shaft shoulder |
| $d_{a \max}$ | 68 mm | Maximum diameter of shaft shoulder |
| $d_{b \min}$ | 71 mm | Minimum shaft shoulder |
| $D_{a \max}$ | 89 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 1,1 mm | Maximum recess radius |
| $r_{a1 \max}$ | 1 mm | Maximum recess radius |

Dimensions

| | | |
|--------------|---------|---------------------------------|
| r_{\min} | 1,1 mm | Minimum chamfer dimension |
| $r_{1 \min}$ | 1 mm | Minimum chamfer dimension |
| s | 2,4 mm | Axial displacement |
| E | 85,5 mm | Raceway diameter outer ring |
| F | 69,5 mm | Raceway diameter inner ring |
| $D_{1 \min}$ | 82,3 mm | Minimum rib diameter outer ring |

Temperature range

| | | |
|------------|--------|----------------------------|
| T_{\min} | -30 °C | Operating temperature min. |
| T_{\max} | 150 °C | Operating temperature max. |

Characteristics

-  F_r Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed