

**FAG****NJ1064-M1** [↗](#)

## Cylindrical roller bearing

Cylindrical roller bearing NJ..-M1, with cage, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type NJ

## Technical information

**Your current product variant**

Design	Standard	
Cage	M1	Two Piece Brass Cage Roller Guided
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

**Main Dimensions & Performance Data**

d	320 mm	Bore diameter
D	480 mm	Outside diameter
B	74 mm	Width
$C_r$	910.000 N	Basic dynamic load rating, radial
$C_{0r}$	1.490.000 N	Basic static load rating, radial
$C_{ur}$	160.000 N	Fatigue load limit, radial
$n_G$	2.200 1/min	Limiting speed
$n_{gr}$	1.300 1/min	Reference speed
$m$	47,62 kg	Weight



### Mounting dimensions

$d_{a \min}$	335 mm	Minimum diameter shaft shoulder
$d_{a \max}$	356 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	465 mm	Maximum diameter of housing shoulder
$d_{c \min}$	380 mm	Minimum shaft shoulder
$r_{a \max}$	3 mm	Maximum recess radius

### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$r_{1 \min}$	4 mm	Minimum chamfer dimension
s	8 mm	Axial displacement
E	440 mm	Raceway diameter outer ring
F	360 mm	Raceway diameter inner ring
$D_{1 \min}$	425,1 mm	Minimum rib diameter outer ring
$d_1$	375,4 mm	Maximum rib diameter inner ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	150 °C	Operating temperature max.

### Characteristics

	Radial load
	Axial load in one direction
	Grease Lubrication
	Oil Lubrication
	Not sealed