



FAG

NUP221-E-XL-TVP2

Cylindrical roller bearing

Cylindrical roller bearing NUP..-E-XL-TVP2, with cage, single row, locating bearing, 2 ribs on outer ring, 1 rib on inner ring, rib washer internal, type NUP

X-life

Technical information



Your current product variant

Design	E	Increased Capacity Design
Cage	TVP2	Solid Window Cage made from PA66
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

Main Dimensions & Performance Data

d	105 mm	Bore diameter
D	190 mm	Outside diameter
B	36 mm	Width
C_r	310.000 N	Basic dynamic load rating, radial
C_{0r}	320.000 N	Basic static load rating, radial
C_{ur}	54.000 N	Fatigue load limit, radial
n_G	5.000 1/min	Limiting speed
n_{gr}	3.400 1/min	Reference speed
$\approx m$	4,2 kg	Weight



Mounting dimensions

d_1	134,5 mm	Maximum rib diameter inner ring
$D_1 \text{ min}$	165,1 mm	Minimum rib diameter outer ring
$d_a \text{ min}$	117 mm	Minimum diameter shaft shoulder
$d_c \text{ min}$	137 mm	Minimum shaft shoulder
$D_a \text{ max}$	178 mm	Maximum diameter of housing shoulder
$r_a \text{ max}$	2,1 mm	Maximum recess radius







Dimensions

r_{min}	2,1 mm	Minimum chamfer dimension
$r_1 \text{ min}$	2,1 mm	Minimum chamfer dimension
E	171,5 mm	Raceway diameter outer ring
F	125,5 mm	Raceway diameter inner ring
B_3	6 mm	Width of loose rib

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed