



FAG


NN3007-D-K-TVP-SP-XL

Cylindrical roller bearing

Super precision cylindrical roller bearings
 NN30..-D-K-TVP-SP, Non-locating bearing,
 double row, with tapered bore, taper 1:12,
 separable, with cage

X-life

Technical information



Your current product variant

Cage	TVP	Plastic cage
Tolerance class	SP	Tolerance class SP
Bore type	K	Tapered, taper 1:12
Change mark	D	Internal Variant D
Radial internal clearance	C1 (Group 1)	Internal clearance smaller than C2
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	35 mm	Bore diameter
D	62 mm	Outside diameter
B	20 mm	Width
C_r	40.500 N	Basic dynamic load rating, radial
C_{0r}	41.500 N	Basic static load rating, radial
C_{ur}	6.700 N	Fatigue load limit, radial
n_G Grease	17.800 1/min	Limiting speed for grease lubrication
n_G Oil	20.900 1/min	Limiting speed for oil lubrication
m	228 g	Weight





Mounting dimensions

d_a	43 mm	Diameter shaft shoulder
	$h12$	Diameter shaft shoulder tolerance
D_a	56,5 mm	Diameter of housing shoulder
	$H12$	Shoulder diameter outer ring clearance
$E_{tk1\ nom}$	53,9 mm	Injection pitch diameter min
$r_{a1\ max}$	1 mm	Maximum recess radius




Dimensions

$r_{1\ min}$	1 mm	Minimum chamfer dimension
E	55 mm	Raceway diameter outer ring
s	1,4 mm	Axial displacement

Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	120 °C	Operating temperature max.

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed