

**SL182913-B-XL**

## Cylindrical roller bearing

Cylindrical roller bearing SL18, full complement roller set, single row, semi-locating bearing, 1 rib on outer ring, 2 ribs on inner ring, type SL18

X-life

## Technical information



## Your current product variant

Design	B	Internal Variant B
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	1	Single-row design

## Main Dimensions &amp; Performance Data

d	65 mm	Bore diameter
D	90 mm	Outside diameter
B	16 mm	Width
$C_r$	67.000 N	Basic dynamic load rating, radial
$C_{0r}$	84.000 N	Basic static load rating, radial
$C_{ur}$	15.400 N	Fatigue load limit, radial
$n_G$	4.900 1/min	Limiting speed
$n_{gr}$	2.550 1/min	Reference speed
$\approx m$	296,5 g	Weight





### Mounting dimensions

$d_{a \min}$	75,7 mm	Minimum diameter shaft shoulder
$d_{c \min}$	75,5 mm	Minimum shaft shoulder
$D_{a \max}$	81 mm	Maximum diameter of housing shoulder
$D_{e \min}$	85 mm	Minimum diameter of housing shoulder
$r_{a \max}$	1 mm	Maximum recess radius
E	85,2 mm	Raceway diameter outer ring

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
s	1 mm	Axial displacement
$d_1$	75,7 mm	Maximum rib diameter inner ring
$D_1 \min$	81 mm	Minimum rib diameter outer ring

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	120 °C	Operating temperature max.

### Characteristics

-  Radial load
-  Axial load in one direction
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed