

**SL024922**

Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Technical information



Your current product variant

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (ISO 492:2023)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	110 mm	Bore diameter
D	150 mm	Outside diameter
B	40 mm	Width
C_r	198.000 N	Basic dynamic load rating, radial
C_{0r}	400.000 N	Basic static load rating, radial
C_{ur}	51.000 N	Fatigue load limit, radial
n_G	2.500 1/min	Limiting speed
n_{gr}	1.600 1/min	Reference speed
m	2,065 kg	Weight

Mounting dimensions

$d_{c \min}$	125 mm	Minimum shaft shoulder
$d_{a \min}$	125 mm	Minimum diameter shaft shoulder
$D_{e \min}$	138 mm	Minimum diameter of housing shoulder
$r_{a \max}$	1,1 mm	Maximum recess radius



Dimensions

r_{\min}	1,1 mm	Minimum chamfer dimension
s	2 mm	Axial displacement
C	20 mm	Distance to lubrication hole
$d_{1 \max}$	125 mm	Maximum rib diameter inner ring
E	138,2 mm	Raceway diameter outer ring

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

NNCL4922V	Bearing designation DIN5412
-----------	-----------------------------

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed