

**SL024948**

Cylindrical roller bearing

Cylindrical roller bearing SL02...-A, full complement roller set, two-row, non-locating bearing, 0 ribs on outer ring (smooth), 3 ribs on inner ring, type SL02

Technical information



Your current product variant

Design	A	Internal Variant A
Radial internal clearance	CN (Group N)	Normal internal clearance
Tolerance class	PN	Normal (PN)
Number of rows	2	Double-row design

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	320 mm	Outside diameter
B	80 mm	Width
C_r	740.000 N	Basic dynamic load rating, radial
C_{0r}	1.700.000 N	Basic static load rating, radial
C_{ur}	198.000 N	Fatigue load limit, radial
n_G	1.110 1/min	Limiting speed
n_{gr}	660 1/min	Reference speed
m	17,24 kg	Weight

Mounting dimensions

$d_{c \min}$	271 mm	Minimum shaft shoulder
$d_{a \min}$	270,6 mm	Minimum diameter shaft shoulder
$D_{e \min}$	299 mm	Minimum diameter of housing shoulder
$r_{a \max}$	2,1 mm	Maximum recess radius



Dimensions

r_{\min}	2,1 mm	Minimum chamfer dimension
s	5 mm	Axial displacement
C	40 mm	Distance to lubrication hole
$d_{1 \max}$	270,6 mm	Maximum rib diameter inner ring
E	299,46 mm	Raceway diameter outer ring

Temperature range






T_{\min}	-30 °C	Operating temperature min.
T_{\max}	120 °C	Operating temperature max.

Additional information

NNCL4948V

Bearing designation DIN5412

Characteristics

	Radial load
	Grease Lubrication
	Oil Lubrication
	Not sealed
	Large bearing