


**SL045008-PP**

## Cylindrical roller bearing

Cylindrical roller bearing SL04...-PP, full complement roller set, two-row, locating bearing, central rib on outer ring, 3 ribs on inner ring, type SL04

## Technical information

**Your current product variant**

|                           |              |                            |
|---------------------------|--------------|----------------------------|
| Sealing                   | PP           | Contact Seal on both sides |
| Radial internal clearance | CN (Group N) | Normal internal clearance  |
| Tolerance class           | PN           | Normal (ISO 492:2023)      |
| Number of rows            | 2            | Double-row design          |

**Main Dimensions & Performance Data**

|                 |             |                                       |
|-----------------|-------------|---------------------------------------|
| d               | 40 mm       | Bore diameter                         |
| D               | 68 mm       | Outside diameter                      |
| B               | 38 mm       | Width                                 |
| $C_r$           | 80.000 N    | Basic dynamic load rating, radial     |
| $C_{0r}$        | 111.000 N   | Basic static load rating, radial      |
| $C_{ur}$        | 16.300 N    | Fatigue load limit, radial            |
| $n_G$<br>Grease | 3.150 1/min | Limiting speed for grease lubrication |
| $\approx m$     | 0,524 kg    | Weight                                |



### Mounting dimensions

|                    |         |  |
|--------------------|---------|--|
| C <sub>a1</sub>    | 28 mm   | Mounting dim for snap ring WRE (not included in delivery)<br>Tolerance: 0/-0,2 |
| C <sub>a2</sub>    | 27 mm   | Mounting dim for retaining ring to DIN 471 (not incl. In delivery) Tol: 0/-0,2 |
| d <sub>1</sub>     | 51,5 mm | Rib diameter inner ring  |
| d <sub>2</sub>     | 55 mm   | Sealing diameter (rib)   |
| d <sub>3</sub>     | 75 mm   | Outside diameter of snap ring WRE  |
| d <sub>1 min</sub> | 51,5 mm | Minimum diameter shaft shoulder  |
|                    | 30 °    | Chamfer angle  |
|                    | -0,2 mm | Lower distance snap ring tolerance   |
|                    | -0,2 mm | Lower distance retaining ring tolerance  |
|                    | 0 mm    | Upper distance snap ring tolerance   |
|                    | 0 mm    | Upper distance retaining ring tolerance  |
|                    | 0 mm    | Lower distance ring groove tolerance   |
|                    | 0,2 mm  | Upper distance ring groove tolerance   |

### Dimensions

|                  |         |                                   |
|------------------|---------|-----------------------------------|
| C                | 37 mm   | Width, outer ring                 |
| C <sub>1</sub>   | 32,2 mm | Distance ring grooves             |
| D <sub>1</sub>   | 65,8 mm | Diameter of groove                |
| m                | 2,7 mm  | Width of groove                   |
| r <sub>min</sub> | 0,6 mm  | Minimum chamfer dimension         |
| t                | 0,8 mm  | Chamfer width                     |
| X                | 28,5 mm | Distance between rolling elements |

### Temperature range

|                  |        |                            |
|------------------|--------|----------------------------|
| T <sub>min</sub> | -20 °C | Operating temperature min. |
| T <sub>max</sub> | 80 °C  | Operating temperature max. |



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Lifetime lubrication, freedom from maintenance



Grease Lubrication



Sealed on both sides