

**HK2820**

## Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

## Technical information



## Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

## Main Dimensions &amp; Performance Data

$F_w$	28 mm	Under roller diameter
D	35 mm	Outside diameter
C	20 mm	Width
$C_r$	20.900 N	Basic dynamic load rating, radial
$C_{0r}$	36.000 N	Basic static load rating, radial
$C_{ur}$	4.700 N	Fatigue load limit, radial
$n_G$	9.200 1/min	Limiting speed
$n_G$ Grease	5.500 1/min	Limiting speed for grease lubrication
$n_{gr}$	6.700 1/min	Reference speed
$\approx m$	36,385 g	Weight

## Dimensions

$C_1$	20 mm	Width, outer ring
$r_{min}$	0,8 mm	Minimum chamfer dimension








### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	140 °C	Operating temperature max.

### Additional information

SD28X35X4	Sealing ring
G28X35X4	Sealing ring 2
LR22X28X20,5	Suitable inner rings LR
IR22X28X20,5-XL	Suitable inner rings IR

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope