

**HK4012**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearings with open ends HK, to DIN 618/ISO 3245

Technical information



Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Type of Seal	Without

Main Dimensions & Performance Data

F_w	40 mm	Under roller diameter
D	47 mm	Outside diameter
C	12 mm	Width
C_r	14.000 N	Basic dynamic load rating, radial
C_{0r}	24.300 N	Basic static load rating, radial
C_{ur}	3.250 N	Fatigue load limit, radial
n_G	6.600 1/min	Limiting speed
n_G Grease	3.950 1/min	Limiting speed for grease lubrication
n_{gr}	5.200 1/min	Reference speed
$\approx m$	29,06 g	Weight

Dimensions

C_1	12 mm	Width, outer ring
r_{min}	0,8 mm	Minimum chamfer dimension



Temperature range

T_{min}	-30 °C	Operating temperature min.
T_{max}	140 °C	Operating temperature max.

Additional information

SD40X47X4	Sealing ring
G40X47X4	Sealing ring 2
LR35X40X12,5	Suitable inner rings LR

Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope