

**HK0808**

Drawn cup needle roller bearing open end

Drawn cup needle roller bearing open end  
HK, single row, with cage

## Technical information



## Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

## Main Dimensions &amp; Performance Data

$F_w$	8 mm	Under roller diameter
D	12 mm	Outside diameter
C	8 mm	Width
$C_r$	2.750 N	Basic dynamic load rating, radial
$C_{0r}$	2.600 N	Basic static load rating, radial
$C_{ur}$	300 N	Fatigue load limit, radial
$n_G$	29.500 1/min	Limiting speed
$n_G$ Grease	17.700 1/min	Limiting speed for grease lubrication
$n_{gr}$	23.800 1/min	Reference speed
$\approx m$	2,5 g	Weight

## Dimensions

$C_1$	8 mm	Width, outer ring
$r_{min}$	0,4 mm	Minimum chamfer dimension



### Temperature range






$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	140 °C	Operating temperature max.

### Additional information

G8X12X3

Sealing ring 2

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope