

**BK2520**

## Drawn cup needle roller bearing closed end

Drawn cup needle roller bearings with closed end BK, to DIN 618/ISO 3245

## Technical information



## Your current product variant

Lubricant	Without
Lubrication hole	Without
Coating	Without
Sealing	Without

## Main Dimensions &amp; Performance Data

$F_w$	25 mm	Under roller diameter
$D$	32 mm	Outside diameter
$C$	20 mm	Width, outer ring
$C_r$	19.900 N	Basic dynamic load rating, radial
$C_{0r}$	33.000 N	Basic static load rating, radial
$C_{ur}$	4.300 N	Fatigue load limit, radial
$n_{G \text{ Grease}}$	6.100 1/min	Limiting speed for grease lubrication
$n_G$	10.200 1/min	Limiting speed
$n_{gr}$	7.400 1/min	Reference speed
$\approx m$	38 g	Weight

## Dimensions

$r_{\min}$	0,8 mm	Minimum chamfer dimension
$C_{t \min}$	17,3 mm	Minimum width to base of drawn cup with closed end








### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	140 °C	Operating temperature max.

### Additional information

SD25X32X4	Sealing ring
G25X32X4	Sealing ring 2
LR20X25X20,5	Suitable inner rings LR
IR20X25X20,5-XL	Suitable inner rings IR

### Characteristics

-  Radial load
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Small design envelope