
**NK60/25-F-XL**

## Needle roller bearing

Needle roller bearing NK..-F-XL, single row,  
no inner ring, outer ring with 2 bords

X-life

## Technical information



## Your current product variant

Lubricant	Without	
Cage	F	Cage of steel
Cage feature	Standard	
Tolerance class	PN	Normal (DIN 620-2)

## Main Dimensions &amp; Performance Data

$F_w$	60 mm	Under roller diameter
D	72 mm	Outside diameter
C	25 mm	Width, outer ring
$C_r$	47.500 N	Basic dynamic load rating, radial
$C_{0r}$	90.000 N	Basic static load rating, radial
$C_{ur}$	15.600 N	Fatigue load limit, radial
$n_G$	7.700 1/min	Limiting speed
$n_{gr}$	4.800 1/min	Reference speed
$\approx m$	184,6 g	Weight

## Dimensions

$r_{min}$	0,6 mm	Minimum chamfer dimension
-----------	--------	---------------------------



### Temperature range

---


$T_{min}$             -30 °C                            Operating temperature min.

$T_{max}$             120 °C                            Operating temperature max.

### Characteristics

---

  $F_r$     Radial load

    Grease Lubrication

    Oil Lubrication

    Not sealed

    Small design envelope