

**NK20/20-XL**

Needle roller bearing

Needle roller bearings NK, light series

X-life

## Technical information

**Ihre aktuelle Produktvariante**

Lubricant	Without	
Cage	Standard	
Cage feature	Standard	
Tolerance class	PN	Normal

**Main Dimensions & Performance Data**

$F_w$	20 mm	Under roller diameter
$D$	28 mm	Outside diameter
$C$	20 mm	Width, outer ring
$C_r$	18.600 N	Basic dynamic load rating, radial
$C_{0r}$	23.800 N	Basic static load rating, radial
$C_{ur}$	4.200 N	Fatigue load limit, radial
$n_G$	21.100 1/min	Limiting speed
$n_{gr}$	12.900 1/min	Reference speed
$m$	0,035 kg	Gewicht

**Dimensions**

$r_{min}$	0,3 mm	Minimum chamfer dimension
-----------	--------	---------------------------








### Temperature range

$T_{min}$	-30 °C	Operating temperature min.
$T_{max}$	120 °C	Operating temperature max.

### Additional information

G20X28X4	Sealing ring
SD20X28X4	Sealing ring 2

### Eigenschaften

-  Radiale Last
-  Fettschmierung
-  Ölschmierung
-  Nicht abgedichtet
-  Kleiner Bauraum