



## Technical information



### Your current product variant

|                           |              |                           |
|---------------------------|--------------|---------------------------|
| Design                    | E1           | Without central rip       |
| Bore type                 | Z            | Cylindrical               |
| Cage                      | TVPB         | Plastic cage              |
| Radial internal clearance | CN (Group N) | Normal internal clearance |
| Relubrication facility    | Standard     |                           |

### Main Dimensions & Performance Data

|          |             |                                   |
|----------|-------------|-----------------------------------|
| d        | 130 mm      | Bore diameter                     |
| D        | 230 mm      | Outside diameter                  |
| B        | 80 mm       | Width                             |
| $C_r$    | 910.000 N   | Basic dynamic load rating, radial |
| $C_{0r}$ | 1.150.000 N | Basic static load rating, radial  |
| $C_{ur}$ | 91.000 N    | Fatigue load limit, radial        |
| $n_G$    | 2.850 1/min | Limiting speed                    |
| $n_{gr}$ | 1.740 1/min | Reference speed                   |
| $m$      | 13,306 kg   | Weight                            |



### Mounting dimensions

|              |        |                                      |
|--------------|--------|--------------------------------------|
| $d_{a \min}$ | 144 mm | Minimum diameter shaft shoulder      |
| $D_{a \max}$ | 216 mm | Maximum diameter of housing shoulder |
| $r_{a \max}$ | 2,5 mm | Maximum recess radius                |

### Dimensions

|            |          |                                    |
|------------|----------|------------------------------------|
| $r_{\min}$ | 3 mm     | Minimum chamfer dimension          |
| $D_1$      | 199,3 mm | Bore diameter outer ring           |
| $d_2$      | 150 mm   | Raceway diameter of the inner ring |
| $d_s$      | 4,8 mm   | Diameter lubrication hole          |
| $n_s$      | 9,5 mm   | Width of lubricating groove        |

### Temperature range

|            |        |                            |
|------------|--------|----------------------------|
| $T_{\min}$ | -30 °C | Operating temperature min. |
| $T_{\max}$ | 120 °C | Operating temperature max. |

### Calculation factors

|       |      |  |
|-------|------|--|
| $e$   | 0,33 | Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y |
| $Y_1$ | 2,07 | Dynamic axial load factor  |
| $Y_2$ | 3,09 | Dynamic axial load factor  |
| $Y_0$ | 2,03 | Static axial load factor   |



## Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Static angular error and misalignment
-  Dynamic angular error and misalignment