



FAG

23148-BE-XL-K

Spherical Roller Bearing

Spherical roller bearings 231...-E1-K, main dimensions to DIN 635-2, with tapered bore, taper 1:12

X-life

Technical information



Your current product variant

Design	BE	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	JPB	Sheet metal cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

Main Dimensions & Performance Data

d	240 mm	Bore diameter
D	400 mm	Outside diameter
B	128 mm	Width
C_r	2.130.000 N	Basic dynamic load rating, radial
C_{0r}	3.150.000 N	Basic static load rating, radial
C_{ur}	255.000 N	Fatigue load limit, radial
n_G	1.700 1/min	Limiting speed
n_{gr}	970 1/min	Reference speed
$\approx m$	60,5 kg	Weight



Mounting dimensions

$d_{a \min}$	257 mm	Minimum diameter shaft shoulder
$d_{a \max}$	276 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	383 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
$d_{b \min}$	254 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	11 mm	Minimum cavity width of the sleeve

Dimensions

r_{\min}	4 mm	Minimum chamfer dimension
D_1	349,9 mm	Bore diameter outer ring
d_2	275,9 mm	Raceway diameter of the inner ring
d_s	9,5 mm	Diameter lubrication hole
n_s	17,7 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,31	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,18	Dynamic axial load factor
Y_2	3,24	Dynamic axial load factor
Y_0	2,13	Static axial load factor

Additional information

H3148X	Adapter sleeve
AH3148	Withdrawal sleeve



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment