



FAG

24044-BE-XL-K30-C3

Spherical Roller Bearing

Spherical roller bearings 240..-BE-K30, main dimensions to DIN 635-2, with tapered bore, taper 1:30

X-life

Technical information



Your current product variant

Design	BE	With lose center lip ring
Bore type	K30	Tapered, taper 1:30
Cage	JPB	Sheet metal cage
Radial internal clearance	C3 (Group 3)	Internal clearance larger than CN
Relubrication facility	Standard	

Main Dimensions & Performance Data

d	220 mm	Bore diameter
D	340 mm	Outside diameter
B	118 mm	Width
C_r	1.620.000 N	Basic dynamic load rating, radial
C_{0r}	2.600.000 N	Basic static load rating, radial
C_{ur}	260.000 N	Fatigue load limit, radial
n_G	1.830 1/min	Limiting speed
n_{gr}	1.090 1/min	Reference speed
$\approx m$	37,725 kg	Weight



Mounting dimensions

$d_{a \min}$	232,4 mm	Minimum diameter shaft shoulder
$D_{a \max}$	327,6 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius

Dimensions

r_{\min}	3 mm	Minimum chamfer dimension
D_1	295,7 mm	Bore diameter outer ring
d_2	245 mm	Raceway diameter of the inner ring
d_s	6,3 mm	Diameter lubrication hole
n_s	12,2 mm	Width of lubricating groove

Temperature range

T_{\min}	-30 °C	Operating temperature min.
T_{\max}	200 °C	Operating temperature max.

Calculation factors

e	0,32	Limiting value of F_a/F_r for the applicability of diff. Values of factors X and Y
Y_1	2,1	Dynamic axial load factor
Y_2	3,13	Dynamic axial load factor
Y_0	2,06	Static axial load factor

Additional information

AH24044	Withdrawal sleeve
---------	-------------------



Characteristics

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Large bearing
-  Static angular error and misalignment
-  Dynamic angular error and misalignment