


## Technical information



### Your current product variant

Design	E1	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	JPA	Sheet metal cage
Radial internal clearance	C4 (Group 4)	Internal clearance larger than C3
Relubrication facility	Standard	



### Main Dimensions & Performance Data

d	100 mm	Bore diameter
D	215 mm	Outside diameter
B	73 mm	Width
$C_r$	810.000 N	Basic dynamic load rating, radial
$C_{0r}$	920.000 N	Basic static load rating, radial
$C_{ur}$	77.000 N	Fatigue load limit, radial
$n_G$	3.300 1/min	Limiting speed
$n_{gr}$	2.380 1/min	Reference speed
$\approx m$	11,71 kg	Weight



### Mounting dimensions

$d_{a \min}$	114 mm	Minimum diameter shaft shoulder
$d_{a \max}$	129 mm	Maximum diameter of shaft shoulder
$D_{a \max}$	201 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$d_{b \min}$	110 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	7 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	184,7 mm	Bore diameter outer ring
$d_2$	130,2 mm	Raceway diameter of the inner ring
$d_s$	6,3 mm	Diameter lubrication hole
$n_s$	12,2 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,33	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,03	Dynamic axial load factor
$Y_2$	3,02	Dynamic axial load factor
$Y_0$	1,98	Static axial load factor

### Additional information

H2320	Adapter sleeve
AHX2320	Withdrawal sleeve



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Static angular error and misalignment



Dynamic angular error and misalignment