

**FAG****22226-E1A-XL-K-M**

Spherical Roller Bearing

Spherical roller bearing 222...-E1A-XL-K-M,  
symmetric 2 outer ribs**X-life**

## Technical information



## Your current product variant

Design	E1A	Without central rip
Bore type	K	Tapered, taper 1:12
Cage	M	Brass Cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

## Main Dimensions &amp; Performance Data

d	130 mm	Bore diameter
D	230 mm	Outside diameter
B	64 mm	Width
C <sub>r</sub>	760.000 N	Basic dynamic load rating, radial
C <sub>0r</sub>	890.000 N	Basic static load rating, radial
C <sub>ur</sub>	81.000 N	Fatigue load limit, radial
n <sub>G</sub>	3.350 1/min	Limiting speed
n <sub>gr</sub>	2.500 1/min	Reference speed
m	10,754 kg	Weight



### Mounting dimensions

$d_{a \min}$	144 mm	Minimum diameter shaft shoulder
$D_{a \max}$	216 mm	Maximum diameter of housing shoulder
$r_{a \max}$	2,5 mm	Maximum recess radius
$d_{a \max}$	151 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	138 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	8 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	3 mm	Minimum chamfer dimension
$D_1$	205 mm	Bore diameter outer ring
$d_2$	151,7 mm	Raceway diameter of the inner ring
$d_s$	6,3 mm	Diameter lubrication hole
$n_s$	12,2 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,26	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	2,62	Dynamic axial load factor
$Y_2$	3,9	Dynamic axial load factor
$Y_0$	2,56	Static axial load factor

### Additional information

H3126	Adapter sleeve
AHX3126	Withdrawal sleeve



### Characteristics

---

-  Radial load
-  Axial load in one direction
-  Axial load in two directions
-  Grease Lubrication
-  Oil Lubrication
-  Not sealed
-  Dynamic angular error and misalignment