



FAG

**23064-BEA-XL-K-MB1**

## Spherical Roller Bearing

Spherical roller bearing 230..-BEA-XL-K-MB1, symmetric 2 outer ribs with rib washer

X-life

## Technical information



## Your current product variant

Design	BEA	With lose center lip ring
Bore type	K	Tapered, taper 1:12
Cage	MB1	Solid brass cage
Radial internal clearance	CN (Group N)	Normal internal clearance
Relubrication facility	Standard	

## Main Dimensions &amp; Performance Data

d	320 mm	Bore diameter
D	480 mm	Outside diameter
B	121 mm	Width
$C_r$	2.300.000 N	Basic dynamic load rating, radial
$C_{0r}$	3.750.000 N	Basic static load rating, radial
$C_{ur}$	330.000 N	Fatigue load limit, radial
$n_G$	1.480 1/min	Limiting speed
$n_{gr}$	920 1/min	Reference speed
$m$	73,285 kg	Weight



### Mounting dimensions

$d_{a \min}$	334,6 mm	Minimum diameter shaft shoulder
$D_{a \max}$	465,4 mm	Maximum diameter of housing shoulder
$r_{a \max}$	3 mm	Maximum recess radius
$d_{a \max}$	357 mm	Maximum diameter of shaft shoulder
$d_{b \min}$	334 mm	Minimum cavity diameter of the sleeve
$B_{a \min}$	13 mm	Minimum cavity width of the sleeve

### Dimensions

$r_{\min}$	4 mm	Minimum chamfer dimension
$D_1$	433 mm	Bore diameter outer ring
$d_s$	9,5 mm	Diameter lubrication hole
$n_s$	17,7 mm	Width of lubricating groove

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	200 °C	Operating temperature max.

### Calculation factors

$e$	0,22	Limiting value of $F_a/F_r$ for the applicability of diff. Values of factors X and Y
$Y_1$	3,01	Dynamic axial load factor
$Y_2$	4,48	Dynamic axial load factor
$Y_0$	2,94	Static axial load factor

### Additional information

H3064-HG	Adapter sleeve
AH3064G-H	Withdrawal sleeve



### Characteristics

---



Radial load



Axial load in one direction



Axial load in two directions



Grease Lubrication



Oil Lubrication



Not sealed



Large bearing



Static angular error and misalignment



Dynamic angular error and misalignment